



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Cameron LED Overbed CMB Series

### Features

The white acrylic front panel provides a soft forward illumination to this contemporary wall mount senior care overbed light. The wood trim accents identify the graceful shape. The Cameron provides both ambient and task light with a four way pull switch, standard (120 volt only). Top diffuser is clear, and bottom diffuser is frosted white acrylic.

### Construction

The ballast/wiring channel is formed from 22-gauge steel and is provided with mounting slots and wiring access. An internal divider provides separate lamp compartments for controlled up light and down light. The decorative frame is fabricated from solid wood. Fixture can mount horizontally only. Power connections can be made in the fixture wiring channel or in a standard junction box (not included).

### Finish

All wood parts are finished high gloss stained cherry or espresso. Internal housing is finished in a lighting grade baked white enamel.

### Diffuser

Diffuser is 0.090" thick matte white acrylic for the front panel and down light, and clear frosted acrylic for up light. Frame mounts to electrical channel with two decorative screws.

### Electrical

Input 120VAC / 60 Hz.  
Not compatible with dimmers.  
Integrated four position pull switch (on up, on down, on both, all off) and single pull switch for nightlight.

### LED

Integrated LED modules capable of producing:  
3 Ft. - 36W, 4050 source lumens total  
4 Ft. - 46W, 5400 source lumens total  
Rated for 50,000 hours, 3000K (CCT), 90 CRI.

### Certification

cETLus listed for indoor damp locations.

### Options

120-277V universal voltage available without switch and nightlight.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

**Specifications and dimensions  
subject to change without notice.**

## Ordering Information:

Cherry	Espresso	LED	Source Lumens	CCT	L	H	D	MC
CMB394000L30ENCH	CMB394000L30ENES	36W	1350 up/2700 down	3000K	39-5/8"	6"	5-3/4"	26-3/4"
CMB515400L30ENCH	CMB515400L30ENES	46W	1800 up/3600 down	3000K	51-5/8"	6"	5-3/4"	38-3/4"

