



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

**Outdoor LED Flood Light**  
**TPDW70050LBK, TPDW110050LBK,**  
**TPDW1300L50BK, TPDW2600L50BK**

**Features**

All purpose long lasting energy saving LED flood light. An excellent alternative solution to incandescent fixtures. Ideal use for security and general lighting in outdoor residential, commercial, and hospitality applications. Fixture can be installed to a standard flood light cover plate (not included).

**Construction**

Housing is made from die-cast aluminum with a durable powder coat. Power supply connections must be made inside a junction box (not included).

**Finish**

Available in black finish.

**Diffuser**

Clear polycarbonate replaceable lens is secured to housing with screws.

**Electrical**

Input 120V VAC / 60 Hz.  
 Not compatible with dimmers.  
 Minimum starting temperature -20°F

**LED**

Integrated LED modules capable of producing:  
 7W, 700 source lumens  
 13.5W, 1300 source lumens  
 20W, 2600 source lumens  
 28W, 4000 source lumens  
 5000K (CCT). Rated for 50,000 Hrs. 80 CRI.

**Certification**

ETL certified for outdoor wet locations.  
 \*ENERGY STAR® Qualified

**Warranty**

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

**Specifications and dimensions**  
 subject to change without notice.

**Ordering Information:**

Black	LED	Source Lumens	CCT	H	W	D
*TPDW70050LBK	7W	700	5000K	4"	8"	5-7/8"
*TPDW1300L50BK	13.5W	1300	5000K	4"	8"	5-7/8"
TPDW2600L50BK	20W	2600	5000K	4"	8"	5-7/8"
TPDW4000L50BK	28W	4000	5000K	4"	8"	5-7/8"

