



Features

- Line voltage - no drivers needed
- Interconnectable kits (3000K Warm White and 6400K Cool White)
- LED Flexbrite consumes only 1 watt per foot
- Dimmable 5-100%*
- UL Listed† for indoor and outdoor use
- 60,000 hours rated life

Available Colors



3000K



6400K

Dimming Options

- ELV (5-100%*)
- LED (5-100%*)
- CL (5-100%*)

Listing / Ratings†



LED Flexbrite Kits

Easy to use flexible, dimmable, and economical LED rope light has UV inhibitor built into the PVC housing for use outdoors. Save 73% in running costs compared to incandescent rope light. LED Flexbrite last up to three times as long as incandescent rope.


Technical Information

Series	LR-LED (Kits)
Input Voltage	120V AC, 60Hz
CCT	3000K (WW) / 6400K (CW)
CRI	67+ (UWW) / 72+ (WW) / 75+ (WH)
Wattage	1W per ft
Lumens	See individual product
Max Run	192 feet (kits)
Cuttable	N/A†
IP Rating	IP65** (uncut), void if cut
Dimmable	5-100%*
Rating	UL Listed† for indoor/outdoor use
Rated Life	60,000 hrs

*Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers.

**IP65 rated only when used with pre-attached molded power cord and end cap is either pre-attached or properly sealed with dielectric grease, silicone and shrink tube

†UL Listing is void if product is cut



TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

LED FLEXBRITE
ROPE LIGHT

ARCHITECTURAL LIGHTING

POWER SUPPLIES



Warm White Kits
120V / 3000K / 72CRI / 32Lm/ft / 1/2" Diameter



Cool White Kits
120V / 6400K / 75CRI / 34Lm/ft / 1/2" Diameter

FLEXBRITE ORDERING INFORMATION

Custom Cut Orders - Please Allow Up To 2-4 Weeks Order Processing & Delivery

ITEM NUMBER	CCT	LENGTH	LUMENS / FT	WATTAGE	IP RATING	CRI	CUTTING
LR-LED-WW-3	3000K	3 ft	32Lm / ft	3W	IP65	67+	N/A
LR-LED-WW-9	3000K	9 ft	32Lm / ft	9W	IP65	67+	N/A
LR-LED-WW-15	3000K	15 ft	32Lm / ft	15W	IP65	67+	N/A
LR-LED-WW-30	3000K	30 ft	32Lm / ft	30W	IP65	67+	N/A
LR-LED-WW-75	3000K	75 ft	32Lm / ft	75W	IP65	67+	N/A
LR-LED-CW-3	6400K	3 ft	34Lm / ft	3W	IP65	75+	N/A
LR-LED-CW-9	6400K	9 ft	34Lm / ft	9W	IP65	75+	N/A
LR-LED-CW-15	6400K	15 ft	34Lm / ft	15W	IP65	75+	N/A
LR-LED-CW-30	6400K	30 ft	34Lm / ft	30W	IP65	75+	N/A
LR-LED-CW-75	6400K	75 ft	34Lm / ft	75W	IP65	75+	N/A

120V Kits Include: (1) Removable 5ft power cord with 1.6A inverter, (1) removable end cap, and (1) mounting clip per foot of rope

FLEXBRITE ACCESSORIES

ITEM NUMBER	DESCRIPTION
LR-LED-EXT3	3' linking cable
RL-TRACK-4	4' clear plastic mounting track
RL-CLIP/SCREW	Clear plastic mounting clips (qty 10)
LR-CLIP-20	Clear plastic mounting clips (qty 20)



LR-LED-EXT3



RL-TRACK-4



RL-CLIP/SCREW
LR-CLIP-20