

Installation manual for: V1800F20

Dimensions:D20" H10" L10

Collection:Primo

Bulb Type:E12 bulb not included

Lamp Frame Weight(1bs):16

Total Weight (1bs):33



Thank you for choosing our product(s).

Our Company is actively involved in every step of the production.

Our product(s) are designed to be utilized for every application that graces your home or business.

We pride ourselves in providing the most prompt and courtesy service to all of the valued customers.

Please find the enclosed detailed instruction and read carefully for proper installation.

If you have any questions, please contact the retailer where the purchased was made.



SAFETY

Warning: MAKE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF. BY EITHER REMOVING THE FUSE OR TURNING OFF THE CIRCUIT BREAKER.


CAUTION

- Before assembling the lighting fixture, please read all instructions carefully.
- All frame & crystal components are fragile, please handle with care.
- Required supply circuit : 110 130V/60Hz
- Labeled wires are "L" for live wire, "N" for neutral wire, "E" for ground wire.
- Never install fixture on damp ceiling, the room should be dry and well ventilated
- All electrical components must be installed by a licensed electrician and in accordance with the National Electrical Code and the appropriate local electrical codes.

Unpack the Package

Please open the box carefully and check all the items are inside the box. If you have any installation, assembling and missing parts questions, where you purchase from and any other relevant information ready, our customer service team will provide comprehensive and worry free service to our valued customers.

Frame Parts List



V1800F20 D20" H10" L10

Step 1

Please use the parts list to ensure you are not missing any parts

V1800F20

PARTS LIST

	1				
part	picture	Description	Parts Number	Qty	Check list
ZA		Crossbar		1	
ZB		13.8"Metal ceiling plate	CP101800R138	1	
ZC		Knurled nut		4	
ZD		Power Cord 20" SPT-1-18# Clear/Gold		1	
P1		Lamp body		1	
P2	0	Connector		1	
Р3		4″Iron bracket		4	
P4		Socket		10	
P5		6"Threaded pipe		1	
Р6		6.2"Metal tube		1	
P7		3.3″Iron bracket		4	


V1800F20	D20"	H10"	L10
V 1000120	$D \triangle U$	1110	1 1 1 1 1

part	picture	Description	Parts Number	Qty	Check list
P8		Cover		2	
Р9		16.2"Bottom		1	
P10	₹	Finial		1	
В		1050-14#*3pcs		84	
С		701-40#*1pc		91	

(0:

(04)

Step 2
Canopy installation instructions



Important: This product must be installed in accordance with the local installation codes by a person familiar with construction and operation of this product and the hazards involved.


- 1. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 2. White wire from ceiling((junction box) attaches to "N"wire from the fixture.
- 3. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 4. Secure mounting bracket to the junction box.
- 5. Insert screws in side of top unit the mounting bracket.

''L'' = Hot wire

"N" = Neutral wire

"E" = Ground wire

Frame Assembly Diagram



Frame Assembly Instructions

Installation:

Please read all instructions carefully.

Before you proceed to install, make sure.

that the power supply is turned off and
remains off until installation is complete.

Please note that each part has been assigned a number.

Please proceed in a numerical order.

- 1. Fix the crossbar (01) on the installation 4" junction-box(J-box).
- 2. Screw the iron bracket (04) on the lamp body (02) pressing holes with M3*12 screws.
- 3. Screw the bottom ring (08) on the iron bracket (04) with M3*8 screws.
- 4. Install the pipe cover (05) into the tier pipe (07) both sides, cover the tier pipe (07) on the threaded pipe (06), then pass the bottom ring (08), scrwe them with tower-shapde (09).
- 5. Make sure the positive and negative charges of wire and lamp body match correctly, screw the connect point with the junction cap.
- 6. Make sure the main wire is enough long and keep the rest wire in the $4^{\prime\prime}$ J-box.
- 7. Fix the lamp body (02) on the crossbar (01) with crossbar bracket (03).
- 8. As the crystal pressing instruction, hang the crystal parts.


The end!

Step 4 Crystal Dressing Instructions

1. Hang crystal "B" "C""

Crystal Dressing Diagram

When dressing the chandelier with the crystals please remember to wear either rubber or cotton gloves. So as to prevent any damage or smudging on the crystals.



Congratulations!

You are now done installing your Elegant Lighting fixture. Sit back and admire each crystal as it will become the statement piece for your room/house.

Thank you.

Cleaning and Maintenance of Chandelier Frame
The finish on our chandelier frames and fixture
frames is protected by a durable coating of
lacquer. To clean, use a clean soft, dry cloth. Do
not use any metal polishes, cleaners, abrasives
or any substance which could remove the
protective finish. Failure to follow these
instructions automatically voids the guarantee.

Cleaning and Maintenance of Crystals
Wet a soft cotton fabric in clean warm water and
wipe gently, then polish with a dry soft cotton
fabric.

To Order Crystal Replacement Parts
Should you require replacement crystals or pins
(the metal connectors attaching the crystals),
contact the store where the product was
purchased. For ease of ordering, you may use the
original crystal trimming instructions provided
with this product and circle the items you wish
to order, indicating the quantity by writing the
number needed adjacent to the circle. You will
be contacted with prices prior to shipment. All
orders must be pre-paid.

Elegant Lighting Warranty

The finish and frame of your new chandelier or fixture are warranted for a period of one (1) year from the date of purchase. Our company will, at its option, repair or replace any frame that has a defect in the materials or workmanship during the warranty period. All crystals are guaranteed for their original quality during the life of the chandelier. Breakage is not covered by this warranty.

To make a claim under this warranty, contact our customer service department. A written return authorization form will be sent to you with specific instructions.

Returns and Conditions of Warranty

Returns must be pre-authorized by contacting the retailer where you made your purchase.. Returns will only be accepted with a written return merchandise authorization and return shipping charges pre-paid. We reseserve the right to inspect all returned merchandise to fully determine the nature of any defect. This guarantee shall not apply to any product that has been changed, altered or otherwise modified, nor shall it apply to any product that has been repaired or altered by anyone other than a pre-authorized facility. We will not be responsible for any breakage or damages incurred during transit, nor for crystal parts or metal frame part that have been subject to misuse, negligence, accident or inappropriate handling. Also, we will not be held responsible for damage incurred during improper installation or wiring by others, nor for damages resulting from a failure to follow the recommended maintenance or installation procedures. This guarantee is issued in lieu of any and all other guaranteed or warrantee, whether written or implied and any and all other obligations or liabilities. Further, we neither authorize nor permit any other person or firm to assume for us, any liability in connection with the sale of our products.