

## Two-Light Outdoor

 Wall mounted • Damp location listed **PROGRESS LED**

### Description:

6" uplight/downlight wall cylinders are ideal for a wide variety of interior and exterior applications including residential and commercial. The aluminum Cylinders offers a contemporary design with its sleek cylindrical form and elegant fade and chip resistant White finish, perfect for today's inspired exteriors. With over 1,500 lumens both up and down the LED Cylinders unite performance, energy savings and safety benefits. Provides even illumination up and down. Specify P860039 top cover lens for use in wet locations.

### Specifications:

- White (-30) (powder coat paint)
- Die cast and extruded aluminum Construction
- White finish.
- Powder coat finish.
- Die-cast aluminum construction with durable powder coated finish
- 1,262 lumens 44 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI
- Meets California Title 24 high efficacy requirements for outdoor use only.
- Dimmable to 10% with many ELV dimmers
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Meets California Title 24 high efficacy requirements for outdoor use only

### Performance:

Number of Modules	2
Input Power	29w per module
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	per module
Lumens/LPW (Delivered)	2566/44.2 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed Meets California Title 24 high efficacy requirements for outdoor use only

## P5642-30/30K

### Images:



### Dimensions:

Width: 6"  
Depth: 8-7/8"  
Height: 18"  
H/CTR: 8"

**P5642-30/30K****Dimming Notes:**

---

P5642 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls**

---

Lutron Diva DVELV-300P

Lutron Nova NTELV-300

Lutron Verti VTELV-600

Lutron MAELV-600

Lutron SPELV-600

Leviton AWRMG-EAW

Leviton 6615-P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.