


LEDme® PRO AC-LED LIGHT BARS

BA-ACLED

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Bringing out the best in bold, eye-catching residential, retail and commercial displays, LEDme® PRO AC-LED Light Bars are ideal for counters and cabinets. Thermally efficient, these fixtures are crafted for illuminating heat sensitive perishables and color sensitive apparel, artwork and collectibles.

FEATURES

- High CRI 90+
- Does not require any driver or transformer
- True 1" profile
- Backlighting with parabolic reflector allows a high uniformity of light
- Each light bar includes one "I" connector
- Minimal space between diffusers for a visually seamless line of illumination
- Free of projected heat, UV and IR radiation
- 90,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS




- Construction:** Extruded aluminum body with polycarbonate lens.
- Power:** Direct 120VAC 60Hz input.
- Light Source:** 2700K or 3000K AC LEDs. CRI: 90.
- Dimming:** May be dimmed down to 10% with electronic low voltage (ELV) dimmer. Compatible with *LUTRON DVELV-300, SELV-300* Electronic Low Voltage dimmer
- Finish:** Abrasion resistant Bronze (BZ), Brushed Aluminum (AL) and White (WT) powder coat.
- Standards:** Title 24 CEC Compliant. ETL & cETL Listed.

FIXTURE PERFORMANCE

Model #	Color Temp	Power	Lumens	Efficacy
BA-ACLED8-927	2700K	5.5W	250	45 Lm/W
BA-ACLED8-930	3000K	5.5W	255	46 Lm/W
BA-ACLED12-927	2700K	8W	360	45 Lm/W
BA-ACLED12-930	3000K	8W	365	46 Lm/W
BA-ACLED18-927	2700K	10W	445	45 Lm/W
BA-ACLED18-930	3000K	10W	450	45 Lm/W
BA-ACLED24-927	2700K	15W	700	47 Lm/W
BA-ACLED24-930	3000K	15W	705	47 Lm/W
BA-ACLED30-927*	2700K	17W	765	45 Lm/W
BA-ACLED30-930*	3000K	17W	785	46 Lm/W

* Not Title 24 compliant


ACCESSORIES

6' power cord 	BA-PC6-WT	Supplies power in any application.
"I" connector 	BA-I-WT	Interconnection for seamless end to end transitions. One included with each light bar.
Interconnect cable 	BA-IC12-WT BA-IC24-WT BA-IC36-WT	12" 24" 36" Links two light bars using a single power connection.

ORDER NUMBER

Model#	Length	Color Temp	Finish
BA-ACLED	8 8"	927 2700K 930 3000K	BZ Bronze AL Brushed Aluminum WT White
	12 12"		
	18 18"		
	24 24"		
	30 30"		

FINISHES



BA-ACLED - -

Example: **BA-ACLED12-927-AL**

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585