TUBE - model: FM-W26 LED Ceiling Mount

WAC LIGHTING

Responsible Lighting®

		0
0		
) •
	 	0

Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Precise engineering using the latest energy efficient LED technology with a built-in reflector for superior optics; An appealing cylindrical profile with a powerful LED down light perfect for accent and wall wash lighting.

FEATURES

- Wall or Ceiling Mount
- IP65 Rated, ETL & cETL wet Location Listed
- Die-Cast Aluminum Construction
- Universal Voltage Input (120V 277V)
- Dimming: ELV (120V) or 0-10V

SPECIFICATIONS

Construction: Aluminum with etched glass. Power: Integral driver in luminaire. 120V - 277V input. Light Source: High output LED Mounting: Mounts directly to junction box Dimming: 0-10V Dimming: 100%-10% ELV Dimming: 100%-5% (120V only) Finish: Brushed Aluminum (AL), Black (BK), Bronze (BZ), Graphite (GH), White (WT) Color Temp: 3000K CRI: 90 Rated Life: 70,000 hours Standards: IP65 Rated, ETL & cETL Wet Location Listed

	Beam	Photometry	Voltage	Watt	Lumens	Finish
	N2612 7y Star® 91°		120V - 277V	30W	1740	AL Brushed Aluminum BK Black
	N2605 1y Star® 33°		120V	16W	800	BZ Bronze GH Graphite WT White
_						

Example: FM-W2612-GH

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. SEP 2017