


PIXELS CCT

Color Temperature Adjustable LED Light Sheet

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Professional flexible light sheet creates uniform and linear illumination. Easy installation in any minimal size application with no heat sink needed. 5 CCTs selectable and best-in-lighting quality make it perfect for applications like bright coves or task lighting in dry or damp locations

FEATURES

- With a lightweight, ultra-thin 1/8" profile
- Select and choose desirable CCT with matching CCT selectable power supply
- Even illumination of translucent surfaces from as little as 1/2" behind
- May be field-cut vertically or horizontally, in unique shapes or around obstructions
- Powers easily by daisy chaining with Gold plated connectors or from any square at soldering points provided
- Versatile Mounting Options:
3M-construction adhesive adheres to most surfaces (flat or curved), or open rectangles indicate where it can be stapled through
- Can be installed in either exposed or fully enclosed spaces
- Specially rated for installation in the storage area of a clothes closet


SPECIFICATIONS

Input: 24VDC
CRI: 90+
McAdams Steps: 3
Color Temp: 2700K / 3000K / 3500K / 4000K / 5000K
Operating Temp: -4°F to 104°F (-20°C to 40°C)
Standards: UL & CUL Listed for Dry and Damp Locations

Model	Dimension	LED Lumens	Watt	Color Temp	Color
LED P05 P10	1224 12" x 24"	500 lm/sq ft 1000 lm/sq ft	5W/sq ft 10W/sq ft	2750 2700K / 3000K / 3500K / 4000K / 5000K	White

LED-P__-1224-__

Example: LED-P10-1224-2750













wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585



Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

	Model	Finish			
	T24-MM-002-WT T24-MM-006-WT	White White	Joiner Cable Connects between Pixels		2 in 6 in
	T24-MM-FLEX-WT	White	I Connector Connects between Pixels		
	T24-TI-WT	White	T Connector Connects Pixels sections		
	T24-XI-WT	White	X Connector Connects Pixels sections		
	T24-LI-WT	White	L Connector Connects Pixels sections		
	T24-FF-WT	White	Joiner Cable Extender Connects joiner cable to joiner cable, female on both sides		
	T24-Y-WT T24-Y-BK	White Black	Flex Y Connector Connects Pixels sections		
	T24-X-WT T24-X-BK	White Black	Flex X Connector Connects Pixels sections		
	T24-IC-002 T24-IC-006 T24-IC-012 T24-IC-036 T24-IC-072 T24-IC-144 T24-IC-240	WT White BK Black	In Wall Rated Joiner Cable Connects Pixels sections, 2 male ends		2 in 6 in 1 ft 3 ft 6 ft 12 ft 20 ft Example: T24-IC-002-WT
	T24-EX3-072 T24-EX3-144 T24-EX3-240 T24-EX3-1200	WT White BK Black	In Wall Rated Extension Cable Extends distance between a hard wire power supply or a wiring box to a Pixels section		6 ft 12 ft 20 ft 100 ft Example: T24-EX3-072-WT

Power Supply

	Model	Input	Output	Dimming	
	PS-24DC-U60R-CS-SM PS-24DC-U96R-CS-SM	120V-277VAC	24VDC 60W 24VDC 96W	ELV / 0-10V	7 11/16" x 3 7/8" x 1 3/8" ≥ 0.9 pf Overload and short circuit protection Includes 6ft lead wire with connector
	PS-24DC-U288R-CSSM	120V-277VAC	24VDC 288W (3 x 96W)	ELV / 0-10V	10 3/4" x 8 5/8" x 1 3/8" ≥ 0.9 pf Overload and short circuit protection Includes 3 x 6ft lead wire connector