2" OCULUX - Adjustable

R2BRA, R2BSA

WAC LIGHTING

Responsible Lighting®





Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Designed to fit in tight plenum space

FEATURES

- Energy Star® Rated
- Title 24 Compliant
- Cutout: 31/16"
- Single spot light source
- Sold as new construction, may be reconfigured in the field for remodel
- ELV or TRIAC or 0-10V dimming compatible

SPECIFICATIONS

Construction: Die-cast aluminum trim with aluminum heat sink

Dimming: 100% - 5% with 0-10V dimmer

100% - 5% with Electronic Low Voltage (ELV) dimmer

Input: 120V AC

Power: 9W, power factor 0.98 **Finish:** Powder coated

Standards: ETL & cETL Listed, damp location listed trims

IC-rated airtight housing

Ceiling thickness: ½" - 1"

Operating Temperature: -4°F to 104°F (20°C to 40°C)

TRIM (SEE NEXT PAGE FOR HOUSING)		Beam	Beam		Color Temp		Lumen	CBCP	Finish	Interior/Trim
		S 15	5°	927 930	2700K 3000K	90 90	535 555	3131 3245	HZWT BN WT	Haze/White Brushed Nickel White
R2BRA Round 0 - 35° Adjustable 45° visual cutoff 3%1e" 2½"	39%6" 5½"	N 25	5°	927 930	2700K 3000K	90 90	635 680	1984 2123	HZWT BN WT	Haze/White Brushed Nickel White
	F 45	5°	927 930	2700K 3000K	90 90	640 685	1053 1127	HZWT BN WT	Haze/White Brushed Nickel White	
		S 15	5°	927 930	2700K 3000K	90 90	535 555	3131 3245	HZWT BN WT	Haze/White Brushed Nickel White
R2BSA Square 0 - 35° Adjustable 45° visual cutoff	2½6" 5½"	N 25	5°	927 930	2700K 3000K	90 90	635 680	1984 2123	HZWT BN WT	Haze/White Brushed Nickel White
	37%	F 45	5°	927 930	2700K 3000K	90 90	640 685	1053 1127	HZWT BN WT	Haze/White Brushed Nickel White

R2BSA-	-	-	-

Example: R2BSA-N930-BN

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760

2" OCULUX - Adjustable

R2BRA, R2BSA


WAC LIGHTING

Responsible Lighting®

INTEGRAL HOUSING AND TRIM: BOTH NEW CONSTRUCTION & REMODEL

NEW CONSTRUCTION CONFIGURATION

IC-Rated, Airtight



REMODEL CONFIGURATION

IC-Rated, Airtight

