OCULUX 2" LED RECESSED R2BRD, R2BSD, R2BRD-11, R2BSD-11

WAC LIGHTING

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	

Location:

PRODUCT DESCRIPTION

Designed to fit in tight plenum space

FEATURES

- Energy Star[®] Rated
- Title 24 Compliant
- Cutout: 31/16"
- Single spot light source
- Sold as new construction, may be reconfigured in the field for remodel
- ELV or TRIAC or 0-10V dimming compatible

SPECIFICATIONS

Construction:	Die-cast aluminum trim with aluminum heat sink
Dimming:	100% - 5% with 0-10V dimmer
	100% - 5% with Electronic Low Voltage (ELV/TRIAC) dimmer
Input:	120V AC
Power:	9W/11W, power factor 0.98
Finish:	Powder coated
Standards:	ETL & cETL Listed, wet location listed trims
	IC-rated airtight housing

Ceiling thickness: 1/2" - 1"

TRIM (SEE NEXT PAGE FOR HOUSING)	Model	Power	Bea	am	Color 1	Гетр	CRI	Lumen	CBCP	Finish	Interior/Trim
<u>()</u> <u>3%16"</u> <u>5½"</u> 2½6"	R2BRD Round Open Reflector	9W	N	25°	927 930	2700K 3000K	90 90	635 680	2277 2437	HZWT	Haze/White Brushed Nickel White
			F	45°	927 930	2700K 3000K	90 90	625 670	1267 1356	BN WT	
	R2BRD-11 Round Open Reflector	11W	N	25°	927 930	2700K 3000K	90 90	885 935	2809 2957	HZWT	Haze/White Brushed Nickel White
			F	45°	927 930	2700K 3000K	90 90	890 940	1623 1708	WT WT	
2½" 3 [%] /6"	R2BSD Square Open Reflector	9W	N	25°	927 930	2700K 3000K	90 90	655 700	2164 2316	HZWT	Haze/White Brushed Nickel White
			F	45°	927 930	2700K 3000K	90 90	645 695	1138 1322	BN WT	
	R2BSD-11 Square 11W Open Reflector	1.11//	N	25°	927 930	2700K 3000K	90 90	890 935	2612 2749	HZWT	Haze/White Brushed Nickel
				F	45°	927 930	2700K 3000K	90 90	905 955	1451 1527	WT

R2BRD-___

Example: R2BRD-11-N930-BN

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050


Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122


Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.

INTEGRAL HOUSING AND TRIM: BOTH NEW CONSTRUCTION & REMODEL

NEW CONSTRUCTION CONFIGURATION *IC-Rated, Airtight*





REMODEL CONFIGURATION

IC-Rated, Airtight

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.