

Sirius

Pendant 3000K

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |

Project:

Location:

| Model & Size | Color Temp & CRI | Finish | | Watt | LED Lumens | Delivered Lumens |
|--------------|------------------|----------------|------------------------------------|------------|----------------------|---------------------|
| PD-81118 18" | 3000K 90 | AL BK WT | Brushed Aluminum Black White | 35W 36W | 2493 1523 2237 | 1218 466 1109 |

Example: PD-81118-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

Full circle. A simple glowing halo completes.

FEATURES

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL, Title 24 JA8-2019 Compliant

Damp Location Listed

Construction: Aluminum body, silicone diffuser

REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



FINISHES:



LINE DRAWING:



PD-81118

1



Sirius

Pendant 3000K

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |

Project:

Location:

| Model & Size | Color Temp & CRI | Finish | Watt | LED Lumens | Delivered Lumens |
|--------------|------------------|---|------------|----------------------|---------------------|
| PD-81124 24" | 3000K 90 | AL Brushed Aluminum BK Black WT White | 49W 48W | 3480 2156 3229 | 1725 623 1555 |

Example: PD-81124-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

Full circle. A simple glowing halo completes.

FEATURES

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL, Title 24 JA8-2019 Compliant

Damp Location Listed

Construction: Aluminum body, silicone diffuser

REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



FINISHES:



LINE DRAWING:





Sirius

Pendant 3000K

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |

Project: Location:

| Model & Size | Color Temp & CRI | Finish | Watt | LED Lumens | Delivered Lumens |
|--------------|------------------|---|------------|----------------------|-------------------------|
| PD-81131 31" | 3000K 90 | AL Brushed Aluminum BK Black WT White | 69W 70W | 4763 3285 4606 | 2054 1139 2024 |

Example: PD-81131-WT

For custom requests please contact customs@waclighting.com

FEATURES

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL,Title 24 JA8-2019 Compliant

Damp Location Listed

Construction: Aluminum body, silicone diffuser

REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



FINISHES:



LINE DRAWING:



PD-81131