

WAC LIGHTING

BLO - 5CCT

Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Lumens	Finish
FM-113	2700K/3000K/3500K	1600	WT White
FM-115	/4000K/5000K 90	2230	

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **FM-113-CS-WT**

DESCRIPTION

Blo LED Flush Mount is designed to blend into any decor with a clean and fresh appearance that produces an abundance of uniform diffused light. Ideal for use in foyers, corridors, hallways, bedrooms, offices, utility work areas, stairways and many other commercial or residential settings. An on-board 5-CCT selectable switch allows you to toggle between different color temperatures to find the perfect setting for your space.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction:	Aluminum with white acrylic diffuser
Power:	27W, 20W
Input:	120 -277 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Installs over a 3" or 4" Junction Box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically powder coated: White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant, ADA, IC, Airtight



FINISHES:



White

LINE DRAWING:

