


DUNE – model: 826
120V Track MR16 Luminaire

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Low Voltage luminaire with die-cast aluminum construction, 350° horizontal rotation and 90° vertical tilt for flexible aiming options.

FEATURES

- Available with LED lamp option
- 350° horizontal rotation and 90° vertical tilt
- Loop back aiming arm for simple adjustments
- Screw on lens cap
- Clear lens included
- Dimmable
- 5 year fixture warranty/3 year LED lamp warranty

SPECIFICATIONS

Construction: Die-cast aluminum fixture with polycarbonate track adapter. Heat resistant rubber grips over rear socket assemblies. Ceramic bi-pin sockets.

Finish: Powder coated Black (BK), White (WT), and Electroplated Brushed Nickel (BN).

Transformer: LED Version - 1W minimum load. Halogen Version - 20W minimum load (1W minimum load available. Consult factory for more details).

Lamp: 826 model uses a 12V MR16, 50W max lamp (not included).
826L model uses 12V MR16, 75W max (not included).
826LED model uses a 12V, 8W MR16 LED lamp (included).
450 lumens, 3000K CCT, 25,000 hour rated life, CRI: 85.

Dimming: With electronic low voltage (ELV) dimmer, LED lamp dims to 10%; Halogen lamp dims to 1%.

Standards: UL & CUL Listed.

ORDER NUMBER

System	Model #	Power	Lamp	Finish
LHT L Track	826LED	8W	LED	BK Black
HHT H Track	826	50W	Halogen	BN Brushed Nickel
JHT J/J2 Track	826L	75W	Halogen	WT White

FINISHES



- -

Example: LHT-826LED-BN

ACCESSORIES

Color Lens	LENS-16-	AMB Amber	UV Filter	LENS-16-UVF
		BLU Blue	Frosted Lens	LENS-16-FR
		GRN Green	Spread Lens	LENS-16-SPR
		RED Red	Beam Elongating Lens	LENS-16-BEL
		YEL Yellow	Honeycomb Louver	LENS-16-HCL

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585