


HR-D417

4" Low Voltage Downlight Trim



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Adjustable gimbal ring trim with dual pin axis.
For use with HR-8400 series low voltage housings.

FEATURES

- Gimbal ring, 25° adjustment from vertical recessed downlight
- Center lamp holder allows lamp to be tilted up to 25° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Handles surfaces up to 3/4" thick
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction. Three heavy gauge retention clips firmly hold trim to housing.

Lamp: Utilizes LED or Halogen 12V MR16 lamps (order separately). 50W or 75W maximum, see individual housing for wattage rating.

Finish: Abrasion resistant powder coat painted or plated metal finish. Available in Black (BK) and White (WT).

Standards: UL & CUL Listed, Suitable for damp locations

ORDER NUMBER

Model # Finish

HR-D417	BN	Brushed Nickel
	WT	White

Model # Finish







HR-D417	-	<input type="text"/>
---------	---	----------------------

Example: **HR-D417-WT**

ACCESSORIES

LENS-16- Color Lens	AMB	Amber	LENS-16-UVF	UV Filter
	BLU	Blue	LENS-16-FR	Frosted Lens
	GRN	Green	LENS-16-SPR	Spread Lens
	RED	Red	LENS-16-BEL	Beam Elongating Lens
	YEL	Yellow	LENS-16-HCL	Honeycomb Louver

4" Low Voltage Housings (Required)

	Model	Voltage	Transformer	Output	Installation	Rating
	HR-8402E	120V	Electronic	12V, 50W max	New Construction	Non-IC
	HR-8402HL*	120V	Magnetic	12V, 75W max	New Construction	Non-IC
	HR-8403	H 120V HF 277V	Magnetic	12V, 50W max	New Construction	IC Airtight
	HR-8402	H 120V HF 277V	Magnetic	12V, 50W max	New Construction	Non-IC
	HR-8401E	120V	Electronic	12V, 50W max	Remodel	Non-IC
	HR-8401	H 120V HF 277V	Magnetic	12V, 50W max	Remodel	Non-IC

*Not Compatible with HR-D418 or HR-D418-S Non-IC housings require 3" of clearance from insulation on all sides.

Accommodates ceiling thickness of up to 3/4" for remodel & 3/4" for new construction.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585