


CUBE ARCHITECTURAL DC-WD05

WAC LIGHTING

LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 5%
 0-10V: 100% - 1%
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite IP65 rated, UL & cUL wet location listed
Standards: Title 24 JA8-2016 Compliant
Operating Temp: -13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color	Temp	CRI	Reference Output ¹			Light Distribution	Finish
							Lumen	CBCP	Efficacy (lm/w)		
DC-WD05	5" 25W x2	S Straight up and down	16°	927S	2700K	90	1825 x 2	10050 x 2	73 x 2		BK Black WT White BZ Bronze GH Graphite
				827S	2700K	85	2190 x 2	12057 x 2	88 x 2		
				930S	3000K	90	1895 x 2	10427 x 2	76 x 2		
				830S	3000K	85	2300 x 2	12644 x 2	92 x 2		
				835S	3500K	85	2350 x 2	12937 x 2	94 x 2		
				840S	4000K	85	2375 x 2	13062 x 2	95 x 2		
		N Straight up and down	25°	927S	2700K	90	1810 x 2	5280 x 2	72 x 2		
				827S	2700K	85	2170 x 2	6335 x 2	87 x 2		
				930S	3000K	90	1880 x 2	5478 x 2	75 x 2		
				830S	3000K	85	2275 x 2	6643 x 2	91 x 2		
				835S	3500K	85	2330 x 2	6797 x 2	93 x 2		
				840S	4000K	85	2350 x 2	6863 x 2	94 x 2		
		F Straight up and down	33°	927S	2700K	90	1900 x 2	4515 x 2	76 x 2		
				827S	2700K	85	2280 x 2	5417 x 2	91 x 2		
				930S	3000K	90	1970 x 2	4685 x 2	79 x 2		
				830S	3000K	85	2390 x 2	5681 x 2	96 x 2		
				835S	3500K	85	2445 x 2	5812 x 2	98 x 2		
				840S	4000K	85	2470 x 2	5870 x 2	99 x 2		
DC-WD0534	5" 17W x2	F Away from the wall	N/A	927A	2700K	90	2000 x 2		80 x 2		
				827A	2700K	85	2400 x 2		96 x 2		
				930A	3000K	90	2075 x 2	N/A	83 x 2		
				830A	3000K	85	2520 x 2		101 x 2		
				835A	3500K	85	2575 x 2		103 x 2		
				840A	4000K	85	2600 x 2		104 x 2		
F Towards the wall	N/A	927B	2700K	90	2000 x 2		80 x 2				
		827B	2700K	85	2400 x 2		96 x 2				
		930B	3000K	90	2075 x 2	N/A	83 x 2				
		830B	3000K	85	2520 x 2		101 x 2				
		835B	3500K	85	2575 x 2		103 x 2				
		840B	4000K	85	2600 x 2		104 x 2				
F One side each	N/A	927C	2700K	90	2000 x 2		80 x 2				
		827C	2700K	85	2400 x 2		96 x 2				
		930C	3000K	90	2075 x 2	N/A	83 x 2				
		830C	3000K	85	2520 x 2		101 x 2				
		835C	3500K	85	2575 x 2		103 x 2				
		840C	4000K	85	2600 x 2		104 x 2				

DC-WD05-_____ - _____ Example: DC-WD05-F930A-WT ¹Reference output shows 25W output. Multiply by 0.7 to determine output for 17W combinations.

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760